

ENDSAM manual

Lucijan Plevnik, Gašper Žerovnik
Jožef Štefan Institute
Jamova cesta 39
SI-1000 Ljubljana
Slovenia

1 Purpose

Program ENDSAM is written in Fortran language. It receives

- a nonnegative number n ,
- a file from a nuclear data library of a certain isotope in ENDF-6 format [1].

Then it

- reads mean values of parameters from File 2 in ENDF-6 format,
- reads covariance data of parameters from File 32 in ENDF-6 format,
- gives information about possible inconsistencies,
- makes n new files in ENDF-6 format which contain values of random samples of resonance parameters in places of original values in File 2.

Moreover,

- if $n = 0$, then only the information about possible inconsistencies is given,
- if there is no File 32 in the processed file, then no output files are created.

2 Input file

ENDSAM reads input data from a file named 'Input' which should be of the form

$$\begin{bmatrix} n \\ File_1 \\ \vdots \\ File_k \end{bmatrix},$$

where n is the number of required samples written in free format and $File_1, \dots, File_k$ is the list of the files in ENDF-6 format to be precessed.

An example of such an input file is

5 ..\\neutrons\\n-011.Na_023.endf ..\\JEFF32N\\n-10-Ne-022.jeff32

3 Restrictions on covariance data

ENDSAM assumes that resonance parameters are governed by the following distributions.

Resonance energy ER : Normal $N(\mu, \sigma^2)$ with density function $f(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$.

All other parameters except fission width GF : Lognormal $LN(\mu, \sigma^2)$ with density

$$g(x) = \begin{cases} \frac{f(\log x)}{x} & : x > 0, \\ 0 & : x \leq 0. \end{cases}$$

Fission width GF :

- If it has positive mean, then lognormal $LN(\mu, \sigma^2)$.
- If it has negative mean, then minus lognormal with density function $g(-x)$.

ENDSAM reads resonance parameters x_1, \dots, x_m and it applies well-known random sampling methods on a collection of normally distributed parameters

$$\tilde{x}_j = \begin{cases} x_j & : x_j \text{ is normal,} \\ \log|x_j| & : x_j \text{ is either lognormal or minus lognormal.} \end{cases}$$

While doing so, the following restrictions of lognormal distribution have to be taken into account. If x_j is lognormal or minus lognormal and $\langle x_j \rangle$, $\sigma(x_j)$ and $ru(x_j)$ respectively stand for its mean, deviation and relative uncertainty, then its data transforms in the following way:

Means:

$$\langle \tilde{x}_j \rangle = \log |\langle x_j \rangle| - \frac{\log(1 + ru(x_j)^2)}{2}$$

Deviations:

$$\sigma(\tilde{x}_j) = \sqrt{\log(1 + ru(x_j)^2)},$$

Correlations:

$$\text{cor}(\tilde{x}_i, \tilde{x}_j) = \begin{cases} \text{cor}(x_i, x_j) \frac{ru(x_j)}{\sqrt{\log(1+ru(x_j)^2)}} & : x_i \text{ is normal,} \\ \frac{\log(1+\text{cor}(x_i, x_j)ru(x_i)ru(x_j))}{\sqrt{\log(1+ru(x_i)^2)\log(1+ru(x_j)^2)}} & : \text{otherwise.} \end{cases} \quad (3.1)$$

It follows from (3.1) that correlations must satisfy

$$\begin{aligned} e^{-\sqrt{\log(1+\text{ru}(x_i)^2)\log(1+\text{ru}(x_j)^2)}} &\leq 1 + \text{cor}(x_i, x_j) \text{ru}(x_i) \text{ru}(x_j) \\ &\leq e^{\sqrt{\log(1+\text{ru}(x_i)^2)\log(1+\text{ru}(x_j)^2)}} \end{aligned} \quad (3.2)$$

if both, x_i and x_j are either lognormal or minus lognormal, while in the case when x_i is normal we get

$$|\text{cor}(x_i, x_j)| \leq \frac{\sqrt{\log(1+\text{ru}(x_j)^2)}}{|\text{ru}(x_j)|}. \quad (3.3)$$

If correlations satisfy equations (3.2) and (3.3), then it is a step in the sampling method to compute a Cholesky decomposition of the matrix $\tilde{C} = [\text{cor}(\tilde{x}_i, \tilde{x}_j)]$. Therefore, it is of fundamental importance that this matrix is positive definite. However, in some nuclear data libraries this is not the case. When this happens, ENDSAM first computes the nearest positive definite correlation matrix of \tilde{C} in Frobenius norm by applying Higham's method [2].

4 Output: information about inconsistencies

ENDSAM throws a warning if any of the following inconsistencies occurs.

- The smallest lower range limit EL for Files 2 and 32 agree, but the highest upper range limit EH in File 32 is greater than that in File 2. In this case energy ranges are treated such as they coincide.
- Given correlation matrix is of size m , but nonzero correlation is given at position (i, j) for $i > m$ or $j > m$. In this case this correlation is ignored.
- A certain parameter has zero deviation, but a nonzero correlation with another parameter. In this case this correlation is ignored.
- A certain parameter has a negative variance or deviation. In this case its sign is changed.
- A certain resonance from File 32 is not found in File 2. In this case parameters of this resonance are not sampled. Resonances are considered to agree if their first parameters coincide up to a relative error of $10^{-3}\%$ and the other parameters coincide up to a relative error of 10%.
- A certain parameter is distributed lognormally and has nonpositive mean or is distributed minus lognormally and has nonnegative mean. In this case this parameter is not sampled.
- Given correlation matrix is not positive definite.

- Certain correlations do not satisfy (3.2) or (3.3). In this case (3.1) is not applied to compute correlations $\text{cor}(\tilde{x}_i, \tilde{x}_j)$, but original correlations $\text{cor}(\tilde{x}_i, \tilde{x}_j) = \text{cor}(x_i, x_j)$ are used instead. ENDSAM gives the number and the list of such correlations.
- Correlation matrix $[\text{cor}(\tilde{x}_i, \tilde{x}_j)]$ is not positive definite. In this case its nearest correlation matrix is computed. ENDSAM gives the number of nonpositive eigenvalues and the smallest eigenvalue.

We have tested ENDSAM by processing files from three major nuclear data laboratories: ENDF/B-VII.1 [3], JEFF 3.2 [4], and JENDL 4.0 [5]. In these libraries, we spotted all the inconsistencies which are listed above. However, we did not find any of the possible inconsistencies which follow, but the program would catch them in order to avoid problems with reading data or computations.

ENDSAM throws an error and moves to the next file on the list if any of the following inconsistencies occurs.

- A certain correlation between resonance parameters has a value which is not between -1 and 1 .
- Flags EL and EH do not satisfy $0 < \text{EL} < \text{EH}$.
- A certain energy range from File 32 was not found in File 2. Energy ranges are considered to agree if the values of EL agree up to a relative error of $10^{-3}\%$ and EH is smaller or equal in File 32 up to the same relative error.
- Corresponding energy ranges from File 2 and File 32 do not have consistent values of flags LRU or LRF.
- The name of ENDF file is longer than '149 minus number of digits of number of samples' characters.
- File with a name from the list in input file was not found.

ENDSAM throws an error and aborts the execution if any of the following occurs. Except for the first one, they are not inconsistencies of the library.

- Certain values of flags appear which are not valid in ENDF-6 format.
- Combinations of values of flags occur which are valid, but not implemented yet:
 - NIS > 1
 - LRU=1 and LRF=4
 - MF=2 and LRU=1 and LRF=7 and KBK $\neq 0$ or KPS $\neq 0$ or KRM $\neq 3$
 - MF=2 and LRU=2 and LRF=1
 - MF=32 and LRU=1 and NRO=1
 - MF=32 and LRU = 1 and LRF=1or2or3 and LCOMP = 1 and NLRS >0 .
- Number of samples is set to be negative.
- Iteration in Higham's method to find nearest correlation matrix does not converge.

5 Output: files in ENDF-6 format

In this section we give an example of input and output file in ENDF-6 format. We process the file of isotope ^{23}Na from ENDF/B-VII.1 library. File 2 is the following.

1.102300+4	2.279200+1	0	0	1	01125	2151	1	
1.102300+4	1.000000+0	0	0	1	01125	2151	2	
6.000000+2	5.000000+5	1	2	0	01125	2151	3	
1.500000+0	5.410000-1	0	0	3	01125	2151	4	
2.279200+1	0.000000+0	0	0	24	41125	2151	5	
2.810000+3	1.000000+0	3.763400+2	3.760000+2	3.530000-1	0.000000+0	1125	2151	6
2.429700+5	1.000000+0	3.295000+2	3.280000+2	1.500000+0	0.000000+0	1125	2151	7
2.983200+5	2.000000+0	2.039000+3	2.038000+3	1.020000+0	0.000000+0	1125	2151	8
5.385700+5	1.000000+0	6.278000+4	6.277000+4	1.014000+1	0.000000+0	1125	2151	9
2.279200+1	0.000000+0	1	0	72	121125	2151	10	
7.617000+3	2.000000+0	6.058000-1	5.800000-3	6.000000-1	0.000000+0	1125	2151	11
3.539000+4	1.000000+0	3.500000+0	1.600000+0	1.900000+0	0.000000+0	1125	2151	12
5.322000+4	2.000000+0	1.112800+3	1.112000+3	7.850000-1	0.000000+0	1125	2151	13
1.174300+5	1.000000+0	3.103000+1	2.680000+1	4.230000+0	0.000000+0	1125	2151	14
1.431300+5	0.000000+0	2.360000+1	1.650000+1	7.100000+0	0.000000+0	1125	2151	15
2.011500+5	1.000000+0	4.927900+3	4.925000+3	2.940000+0	0.000000+0	1125	2151	16
2.143000+5	0.000000+0	1.428500+4	1.428000+4	4.640000+0	0.000000+0	1125	2151	17
2.390500+5	2.000000+0	5.350200+3	5.349000+3	1.200000+0	0.000000+0	1125	2151	18
2.994100+5	1.000000+0	1.325600+2	1.300000+2	2.560000+0	0.000000+0	1125	2151	19
3.923200+5	1.000000+0	2.277000+4	2.276000+4	9.870000+0	0.000000+0	1125	2151	20
5.980000+5	1.000000+0	2.580000+4	2.580000+4	0.000000+0	0.000000+0	1125	2151	21
7.270000+5	3.000000+0	4.500000+4	4.500000+4	0.000000+0	0.000000+0	1125	2151	22
2.279200+1	0.000000+0	2	0	42	71125	2151	23	
1.900600+5	0.000000+0	2.750000+1	1.820000+1	9.300000+0	0.000000+0	1125	2151	24
2.367100+5	2.000000+0	6.679000+1	6.520000+1	1.590000+0	0.000000+0	1125	2151	25
3.052000+5	0.000000+0	7.800000+1	6.830000+1	9.700000+0	0.000000+0	1125	2151	26
4.309000+5	0.000000+0	4.005300+3	4.000000+3	5.290000+0	0.000000+0	1125	2151	27
4.488200+5	2.000000+0	7.029500+3	7.026000+3	3.520000+0	0.000000+0	1125	2151	28
6.970000+5	4.000000+0	6.000000+4	6.000000+4	0.000000+0	0.000000+0	1125	2151	29
7.800000+5	4.000000+0	4.400000+4	4.400000+4	0.000000+0	0.000000+0	1125	2151	30
0.000000+0	0.000000+0	0	0	0	01125	2	099999	

After reading this file, ENDSAM lets us know that there are 23 resonances in File 2. Indeed, they appear in the lines 6 – 9, 11 – 22, and 24 – 30.

1.102300+4	2.279200+1	0	0	1	0112532151	1	
1.102300+4	1.000000+0	0	0	1	0112532151	2	
6.000000+2	5.000000+5	1	2	0	0112532151	3	
1.500000+0	5.410000-1	0	2	0	0112532151	4	
2.279200+1	0.000000+0	0	0	276	23112532151	5	
2.810000+3	1.000000+0	3.763400+2	3.760000+2	3.530000-1	0.000000+0	112532151	6
4.013280+0	0.000000+0	0.000000+0	6.998690+0	6.800100-3	0.000000+0	112532151	7
7.617000+3	2.000000+0	6.058000-1	5.800000-3	6.000000-1	0.000000+0	112532151	8

1.142550+1	0.000000+0	0.000000+0	4.640000-4	6.000000-2	0.000000+0	112532151	9
3.539000+4	1.000000+0	3.500000+0	1.600000+0	1.900000+0	0.000000+0	112532151	10
2.117700+0	0.000000+0	0.000000+0	1.730000-1	2.100000-1	0.000000+0	112532151	11
5.322000+4	2.000000+0	1.112800+3	1.112000+3	7.850000-1	0.000000+0	112532151	12
4.979462+1	0.000000+0	0.000000+0	3.500280+1	7.800000-2	0.000000+0	112532151	13
1.174300+5	1.000000+0	3.103000+1	2.680000+1	4.230000+0	0.000000+0	112532151	14
1.100659+2	0.000000+0	0.000000+0	1.145000+1	7.100000-1	0.000000+0	112532151	15
1.431300+5	0.000000+0	2.360000+1	1.650000+1	7.100000+0	0.000000+0	112532151	16
1.402086+2	0.000000+0	0.000000+0	2.250000+0	4.900000-1	0.000000+0	112532151	17
1.900600+5	0.000000+0	2.750000+1	1.820000+1	9.300000+0	0.000000+0	112532151	18
1.901000+2	0.000000+0	0.000000+0	5.216000+0	1.268000+0	0.000000+0	112532151	19
2.011500+5	1.000000+0	4.927900+3	4.925000+3	2.940000+0	0.000000+0	112532151	20
2.010000+2	0.000000+0	0.000000+0	3.760036+2	9.550000-1	0.000000+0	112532151	21
2.143000+5	0.000000+0	1.428500+4	1.428000+4	4.640000+0	0.000000+0	112532151	22
2.093280+2	0.000000+0	0.000000+0	8.867000+2	7.600000-1	0.000000+0	112532151	23
2.367100+5	2.000000+0	6.679000+1	6.520000+1	1.590000+0	0.000000+0	112532151	24
2.391377+2	0.000000+0	0.000000+0	1.210000+1	3.000000-1	0.000000+0	112532151	25
2.390500+5	2.000000+0	5.350200+3	5.349000+3	1.200000+0	0.000000+0	112532151	26
2.391500+2	0.000000+0	0.000000+0	9.980000+1	2.060020-1	0.000000+0	112532151	27
2.429700+5	1.000000+0	3.295000+2	3.280000+2	1.500000+0	0.000000+0	112532151	28
2.405601+2	0.000000+0	0.000000+0	1.620000+1	4.130000-1	0.000000+0	112532151	29
2.983200+5	2.000000+0	2.039000+3	2.038000+3	1.020000+0	0.000000+0	112532151	30
2.986500+2	0.000000+0	0.000000+0	4.875000+1	1.342000-1	0.000000+0	112532151	31
2.994100+5	1.000000+0	1.325600+2	1.300000+2	2.560000+0	0.000000+0	112532151	32
2.995400+2	0.000000+0	0.000000+0	6.724000+0	4.270000-1	0.000000+0	112532151	33
3.052000+5	0.000000+0	7.800000+1	6.830000+1	9.700000+0	0.000000+0	112532151	34
2.993018+2	0.000000+0	0.000000+0	9.820000+0	1.940000+0	0.000000+0	112532151	35
3.923200+5	1.000000+0	2.277000+4	2.276000+4	9.870000+0	0.000000+0	112532151	36
3.909906+2	0.000000+0	0.000000+0	2.276000-1	2.700037+0	0.000000+0	112532151	37
4.309000+5	0.000000+0	4.005300+3	4.000000+3	5.290000+0	0.000000+0	112532151	38
4.315300+2	0.000000+0	0.000000+0	6.780000+2	6.970000-1	0.000000+0	112532151	39
4.488200+5	2.000000+0	7.029500+3	7.026000+3	3.520000+0	0.000000+0	112532151	40
4.497200+2	0.000000+0	0.000000+0	1.400000-1	5.860140-1	0.000000+0	112532151	41
5.385700+5	1.000000+0	6.278000+4	6.277000+4	1.014000+1	0.000000+0	112532151	42
4.411600+2	0.000000+0	0.000000+0	4.135000+4	2.000014+0	0.000000+0	112532151	43
5.980000+5	1.000000+0	2.580000+4	2.580000+4	0.000000+0	0.000000+0	112532151	44
2.990000+3	0.000000+0	0.000000+0	3.800048+3	0.000000+0	0.000000+0	112532151	45
6.970000+5	4.000000+0	6.000000+4	6.000000+4	0.000000+0	0.000000+0	112532151	46
3.418000+3	0.000000+0	0.000000+0	9.600000+3	0.000000+0	0.000000+0	112532151	47
7.270000+5	3.000000+0	4.500000+4	4.500000+4	0.000000+0	0.000000+0	112532151	48
3.598613+3	0.000000+0	0.000000+0	7.200000+3	0.000000+0	0.000000+0	112532151	49
7.800000+5	4.000000+0	4.400000+4	4.400000+4	0.000000+0	0.000000+0	112532151	50
3.888800+3	0.000000+0	0.000000+0	7.040000+3	0.000000+0	0.000000+0	112532151	51
0.000000+0	0.000000+0	3	69	0	0112532151	52	
0.000000+0	0.000000+0	0	0	0	0112532	099999	

Here, ENDSAM returns that there are 69 resonance parameters with covariance data, out of which 65 are nonconstant. Indeed, their mean values appear in columns 1, 4, and 5

of even lines from 6 to 50, while their deviations appear one line below mean values. Zero deviations of parameters with covariance data thus appear in column 5 of lines 45, 47, 49, and 51.

Next, ENDSAM informs us that correlation matrix equals identity matrix which can be seen from zero value in column 5 of line 52.

The next step is to make random samples and in the end their values are written to new files in ENDF-6 format. If original file has the name File.ext and n is the number of samples, then sampled files have names File_1.ext, ..., File_n.ext. Below we give an example of File 2 which contains sampled values.

1.102300+4	2.279200+1	0	0	1	01125	2151	1
1.102300+4	1.000000+0	0	0	1	01125	2151	2
6.000000+2	5.000000+5	1	2	0	01125	2151	3
1.500000+0	5.410000-1	0	0	3	01125	2151	4
2.279200+1	0.000000+0	0	0	24	41125	2151	5
2.811069+3	1.000000+0	3.763400+2	3.704244+2	3.664647-1	0.000000+01125	2151	6
2.428422+5	1.000000+0	3.295000+2	3.225574+2	1.605526+0	0.000000+01125	2151	7
2.980303+5	2.000000+0	2.039000+3	2.024915+3	8.057385-1	0.000000+01125	2151	8
5.379616+5	1.000000+0	6.278000+4	6.362465+4	8.786140+0	0.000000+01125	2151	9
2.279200+1	0.000000+0	1	0	72	121125	2151	10
7.612944+3	2.000000+0	6.058000-1	5.523922-3	5.520258-1	0.000000+01125	2151	11
3.538575+4	1.000000+0	3.500000+0	1.583915+0	1.795089+0	0.000000+01125	2151	12
5.324757+4	2.000000+0	1.112800+3	1.143244+3	6.466060-1	0.000000+01125	2151	13
1.175479+5	1.000000+0	3.103000+1	3.865670+1	3.165214+0	0.000000+01125	2151	14
1.429167+5	0.000000+0	2.360000+1	1.616699+1	6.442193+0	0.000000+01125	2151	15
2.014819+5	1.000000+0	4.927900+3	5.062836+3	3.339159+0	0.000000+01125	2151	16
2.142452+5	0.000000+0	1.428500+4	1.510024+4	4.793710+0	0.000000+01125	2151	17
2.391225+5	2.000000+0	5.350200+3	5.387397+3	1.256445+0	0.000000+01125	2151	18
2.992458+5	1.000000+0	1.325600+2	1.224137+2	2.427136+0	0.000000+01125	2151	19
3.924053+5	1.000000+0	2.277000+4	2.275973+4	1.304718+1	0.000000+01125	2151	20
5.992946+5	1.000000+0	2.580000+4	3.042950+4	0.000000+0	0.000000+01125	2151	21
7.312937+5	3.000000+0	4.500000+4	3.938414+4	0.000000+0	0.000000+01125	2151	22
2.279200+1	0.000000+0	2	0	42	71125	2151	23
1.900883+5	0.000000+0	2.750000+1	2.167164+1	1.024670+1	0.000000+01125	2151	24
2.365003+5	2.000000+0	6.679000+1	8.986865+1	1.741793+0	0.000000+01125	2151	25
3.052484+5	0.000000+0	7.800000+1	6.933420+1	1.021129+1	0.000000+01125	2151	26
4.308275+5	0.000000+0	4.005300+3	4.092822+3	5.787986+0	0.000000+01125	2151	27
4.488591+5	2.000000+0	7.029500+3	7.026158+3	3.618211+0	0.000000+01125	2151	28
6.914366+5	4.000000+0	6.000000+4	7.335487+4	0.000000+0	0.000000+01125	2151	29
7.823972+5	4.000000+0	4.400000+4	5.083665+4	0.000000+0	0.000000+01125	2151	30
0.000000+0	0.000000+0	0	0	0	01125	2	099999

References

- [1] Cross Sections Evaluation Working Group (Edited by M. Herman and A. Trkov), "ENDF-6 Formats Manual, Data formats and procedures for the Evaluated Nuclear

- Data File ENDF/B-VI and ENDF/BVII," *Document ENDF-102, Report BNL-90365-2009, Rev. 2*, National Nuclear Data Center (NNDC), Brookhaven National Laboratory, Upton, USA, November 2011.
- [2] N. J. Higham, Computing the nearest correlation matrix - a problem from finance, *IMA Journal of Numerical Analysis*, **22** (2002), 329–343.
 - [3] M.B. Chadwick, et. al., "ENDF/B-VII.1 Nuclear Data for Science and Technology: Cross Sections, Covariances, Fission Product Yields and Decay Data," *Special Issue on ENDF/B-VII.1 Library, Nucl. Data Sheets (N.Y. N.Y.)*, **112** (2011), 2887–2996.
 - [4] https://www.oecd-nea.org/dbforms/data/eva/evatapes/jeff_32/
 - [5] K. Shibata, et. al., "JENDL-4.0: A New Library for Nuclear Science and Engineering," *J. Nucl. Sci. Technol.*, **48** (2011), 1–30.